




Cabin Fever Quilts & LaRue's Country Quilts

• 435-257-0801 • www.aPatternGal.com

145 W. Main ~ Tremonton, UT 84337 Your Quilting Headquarters

© 9/2005, RaMel Enterprises, Inc. These instructions are for personal use only and are part of a kit. No part may be used for profit without prior written permission.

Hot Pad Quilt Blocks #7 Jewel Box



8.5" unfinished

General Piecing Rules For This Block Style:

- Sew and press seams away from the center.
- Sew scant $\frac{1}{4}$ " seam allowances, do not open seams.
- Strip sew, then cut into segments.
- Simple 9 patch

Fabric Requirements

- A. Triangle Centers: $4 \frac{7}{8}$ " sq. + $4, 2 \frac{1}{2}$ " sq. = 10.5 " x 5 "
- B. 4 Patch: $4, 2 \frac{1}{2}$ " square = 10.5 " x 2.5 "
- C. Triangles: $4 \frac{7}{8}$ " sq. = 5 " square.


Quilt Block Outside Border to make a 10" square: 1.5" x 42"
Additional Hotpad Requirements: 1 fat 16th back fabric & 8.5" square batting.

Block Assembly:

1. Square up A&C to $4 \frac{7}{8}$ ". Next cut A 5 " sq. in half leaving $2, 2 \frac{1}{2}$ " x 5 " strips.
2. Sew AB strips together and cut into $4, 2 \frac{1}{2}$ " sections.
 - a. Flip one and sew two four patches together.
3. Using 2 part triangle method listed below draw lines and sew AC $4 \frac{7}{8}$ " squares. Finger press.
4. As shown in diagram, sew a four patch next to A side of two part triangle squares and complete block as shown.
5. Press and square up block to 8.5 ".

METHODS

2 Part Triangle Squares. Draw diagonal line down the center of square. Draw two more lines $\frac{1}{4}$ " from the center line. Sew down outside lines and cut block apart down the center line after sewing.



Sandwich, Pre-binding Hotpads. = Layer 100% Cotton W&N Batting square on bottom. Place back fabric face up onto batting, then place pieced block face down on top of back. Pin if needed and stitch around all four sides leaving a 2 "- 3 " turning opening. Trim corners and turn right sides out. Then blind hem opening closed.